

CSCE 574 ROBOTICS

Computer Vision

Slides courtesy of Professor Gregory Dudek
Alberto Quattrini Li
albertoq@cse.sc.edu



Why vision?

- Passive (emits nothing).
 - Discreet.
 - Energy efficient.
- Intuitive.
- Powerful (works well for us, right?)
- Long and short range.
- Fast.



So, what's the problem?

How hard is vision? Why do we think is do-able?

Problems:

- Slow.
- Data-heavy.
- Impossible.
- Mixes up many factors.



Data heavy



From GoPro HERO3+ at Barbados 2015 Field Trials






Aliasing

- Images are not actually continuous.
- The sampling (and hardware) issues lead to a few other minor problems.




Aliasing






Aliasing



- To avoid: $f_{sampling} > 2F_{max}$
 - Nyquist Rate



Aliasing: Moiré Patterns





What a camera does to the 3d world...

Shigeo Fukuda



squeezes away one dimension



What a camera does to the 3d world...

Shigeo Fukuda



http://www.psychologie.tu-dresden.de/i1/kaw/diverses Material/www.illusionworks.com/html/art_of_shigeo_fukuda.html

• In trying to extract 3d structure from 2d images, vision is an *ill-posed* problem.





 In trying to extract 3d structure from 2d images, vision is an *ill-posed* problem.








 In trying to extract 3d structure from 2d images, vision is an ill-posed problem.







 An image isn't enough to disambiguate the many possible 3d worlds that could have produced it.



Difficult scenarios

 In certain settings, such as the underwater, robotic vision is particularly challenging

- Different lighting conditions
- Color loss
- Hazing and blur
- Texture loss





What does a robot need?

doesn't need a full interpretation of available images

"This is Prof. X in his office offering me a cup of iced tea."

does need information about what to do...

"Run Away!!"

•avoiding obstacles (or predators)
•pursuing objects
•localizing itself
•Mapping
•finding targets
•reasoning about the world ...

environmental interactions



Key problems

- Recognition:
 - What is that thing in the picture?
 - What are all the things in the image?
- Scene interpretation
 - Describe the image?
- Scene "reconstruction":
 - What is the 3-dimensional layout of the scene?
 - What are the physical parameters that gave rise to the image?
 - What is a description of the scene?

Notion of an "inverse problem."



Robot vision sampler

A brief overview of robotic vision processing...


(1) Image streams simplified via generality simplified via specificity

- (2) Stereo vision ——— (or beyond...)
- (3) Incorporating vision within robot control

 3d reconstruction Visual "servoing"




3d reconstruction





Visual Servoing





Computer vision algorithms


- Image processing
- Geometric computer vision
- Semantic computer vision


It is fundamental first to understand image formation



Camera Geometry


$3D \rightarrow 2D$ transformation: perspective projection








Coordinate Systems






Coordinate Systems





From 3d to 2d



$$x = \frac{fX}{Z} \qquad y = \frac{fY}{Z}$$

a nonlinear transformation

goal: to recover information about (X,Y,Z) from (x,y)



Camera Calibration

- Camera Model
 - [*u v 1*] Pixel coords
 - $-\begin{bmatrix} x_w & y_w & z_w & 1 \end{bmatrix}^T$ World coords


$$z_{c} \begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = A \begin{bmatrix} R & T \end{bmatrix} \begin{bmatrix} x_{w} \\ y_{w} \\ z_{w} \\ 1 \end{bmatrix}$$


- Intrinsic Parameters
 - $-\alpha_x = f \cdot m_x, \alpha_y = f \cdot m_y$ focal lengths in pixels
 - γ skew coefficient
 - $-u_0, v_o$ focal point
- Extrinsic Parameters
 - $-[R \ T]$ Rotation and Translation



 $A = \begin{bmatrix} \alpha_x & \gamma & u_0 \\ 0 & \alpha_y & v_o \\ 0 & 0 & 1 \end{bmatrix}$

Camera Calibration





Existing packages in MATLAB, OpenCV, etc



Rectified Image Sample

Unrectified

Rectified



From Clearpath Husky Axis M1013 camera





Rectified Image Sample

Unrectified

Rectified



From Parrot ARDrone 2.0 front camera







Rectified Image Sample

Unrectified

Rectified





From GoPro HERO3+ at Barbados 2015 Field Trials




ReRectified Image Sample

Rectified




From Aqua front camera at Barbados 2013 Field Trials

ReRectified





Gaussian Blur









Gaussian Blur and Noise





CSCE 574: Robotics

Gaussian Blur, Noise, Sobel







Image Downsampling








Thresholded image





Edge detection





Correspondence Problem






37

From Raspberry PI camera at Barbados 2016 Field Trials




Correspondence






Fiduciary Markers/Fiducial





(a) MaxiCode

(b) DataMatrixSymbol





(c) ARToolkit

(d) ARTag



CSCE 574: Robotics


Fourier Tag


Good Feature

- Invariant to transformations
- Unique
- Efficient to compute
- Good precision and high recall
- Several Alternatives:
 - Harris Corners (OpenCV)
 - SURF (OpenCV)
 - SIFT
 - ORB
 - etc




Harris Corners








Harris Corners






Harris Corners






SIFT






SIFT






SURF






SURF






ORB






ORB






Outliers






Mosaic





3D Sparse reconstruction





3D Sparse reconstruction

Source: https://grail.cs.washington.edu/rome/







Internet Photos ("Colosseum")

Reconstructed 3D cameras and points






















Egomotion



$$C_1 M_1(T \times RC_2 M_2) = 0$$



Visual Odometry/Structure from Motion






• Definition:


 the pattern of apparent motion of objects, surfaces, and edges in a visual scene caused by the relative motion between an observer (an eye or a camera) and the scene.



Optical Flow Field












Information about *image motion* rather than the *scene*. This is a classic **reconstruction** problem.


This next step might be to use the image motion to infer scene motion, robot motion or 3D layout.










Information about scene motion rather than the scene.













an "image cube"

I(x,y,t)




Information about scene motion rather than the scene.















optical flow


How?




By measuring the direction that intensities are moving...
 I(x,y,t)













90 90 70 40 25 90 70 40 40 25 90 70 40 40 25 90 70 40 40 20 70 50 40 30 15


We can estimate things...





By measuring the direction that intensities are moving...











1(x,y,1)

90 90 70 40 25

90 70 40 40 25

90 70 40 40 25

90 70 40 40 20


70 50 40 30 15


We can estimate things ...


$$\frac{dI}{dx} = I_x \text{ at } (0,0,0)$$





By measuring the direction that intensities are moving...











90 90 70 40 25 90 70 40 40 25 90 70 40 40 25 90 70 40 40 25 90 70 40 40 20 70 50 40 30 15

I(0,0,1)


We can estimate things like


$$\frac{dI}{dx} = I_x \text{ at } (0,0,0) = \frac{\Delta I}{\Delta x} =$$


$$= \frac{\Delta I}{\Delta x} = \frac{I(1,0,0) - I(0,0,0)}{1 - 0} = -30$$





By measuring the direction that intensities are moving...











90 90 70 40 25 90 70 40 40 25 90 70 40 40 25 90 70 40 40 25 90 70 40 40 20 70 50 40 30 15

I(0,0,1)

We can estimate things like

$$\frac{dI}{dx} = I_x$$

$$\frac{dI}{dy} = I_y$$

68

Let I(x,y,t) be the sequence of images.

(x,y,t

Simplest assumption (constant brightness constraint)

$$I(x,y,t) = I(x + dx, y + dy, t + dt)$$

99 90 90 70 40 95 90 70 40 40 90 90 70 40 40 90 90 70 40 40 90 70 50 40 30



Let I(x,y,t) be the sequence of images.

(x,y,t)

Simplest assumption (constant brightness constraint).

$$I(x,y,t) = I(x + dx, y + dy, t + dt)$$

99 90 90 70 40 95 90 70 40 40 90 90 70 40 40 90 90 70 40 40 90 70 50 40 30

Reminder: $f(x + dx) = f(x) + f'(x) dx + f''(x) dx^2/2 + ...$



Let I(x,y,t) be the sequence of images.

(x,y,t

Simplest assumption (constant brightness constraint).

$$I(x,y,t) = I(x + dx, y + dy, t + dt)$$

99 90 90 70 40 95 90 70 40 40 90 90 70 40 40 90 90 70 40 40 90 70 50 40 30

Reminder:
$$f(x + dx) = f(x) + f'(x) dx + f''(x) dx^2/2 + ...$$

$$I(x,y,t) = I(x,y,t) + I_x dx + I_y dy + I_t dt + 2nd deriv. + higher$$



Let I(x,y,t) be the sequence of images.

(x,y,t)

Simplest assumption (constant brightness constraint).

$$I(x,y,t) = I(x + dx, y + dy, t + dt)$$

99 90 90 70 40 95 90 70 40 40 90 90 70 40 40 90 90 70 40 40 90 70 50 40 30

Reminder:
$$f(x + dx) = f(x) + f'(x) dx + f''(x) dx^2/2 + ...$$

$$I(x,y,t) = I(x,y,t) + I_x dx + I_y dy + I_t dt + 2nd deriv. + higher$$

$$0 = I_x dx + I_y dy + I_t dt$$





Measuring Optical Flow

Let I(x,y,t) be the sequence of images.

(x,y,t)

Simplest assumption (constant brightness constraint).

$$I(x,y,t) = I(x + dx, y + dy, t + dt)$$

99 90 90 70 40 95 90 70 40 40 90 90 70 40 40 90 90 70 40 40 90 70 50 40 30

Reminder:
$$f(x + dx) = f(x) + f'(x) dx + f''(x) dx^2/2 + ...$$

$$I(x,y,t) = I(x,y,t) + I_x dx + I_y dy + I_t dt + 2nd deriv. + higher$$

$$0 = I_x dx + I_y dy + I_t dt$$

$$-I_t = I_x \frac{dx}{dt} + I_y \frac{dy}{dt}$$

intensity-flow equation


good and bad...




The "aperture" problem

$$-I_{t} = I_{x} \frac{dx}{dt} + I_{y} \frac{dy}{dt}$$

- The intensity-flow equation provides only one constraint on *two* variables (x-motion and y-motion)
- → It is only possible to find optical flow in one direction...








The "aperture" problem

→ It is only possible to find optical flow in one direction...

at any single point in the image!



Smoothing can be done by incorporating neighboring points' information.



Observations & Warnings

- Assume the scene itself is static.
- Find matching chunks in the images.
- An instance of *correspondence*.

BUT

- World really isn't static.
- Lightning might change even in a static scene.




Features vs Optical Flow

- Feature-based methods
 - Detect features (corners, textured areas), extract descriptors, and track them
 - Sparse motion fields, but possibly robust tracking
 - Suitable especially when image motion is large (10s of pixels)
- Direct methods (optical flow)
 - Directly recover image motion from spatio-temporal image brightness variations
 - Global motion parameters directly recovered without an intermediate feature motion calculation
 - Dense motion fields, but more sensitive to appearance variations
 - Suitable for video and when image motion is small (< 10 pixels)



Camera and IMU

From drifter with Raspberry PI Camera and Pololu MinIMU-9 v3 at Barbados 2016 Field Trials






A Vision "solution"

• If interpreting a single image is difficult... What about more ?!







multiple cameras






multiple times




Stereo Vision: Pinhole Camera






Stereo Vision: Pinhole Camera






Stereo Vision: Pinhole Camera






Stereo Vision: Pinhole





Stereo Vision: Pinhole




$$\frac{p_{x1}}{f} = \frac{a_1}{D}$$


$$\frac{p_{x2}}{f} = \frac{a_2}{D}$$

$$a_1 + a_2 = b$$



Baseline





•What's the optimal baseline?

Too small: large depth error

Too large: difficult search problem



Baseline

GoPro 3D HERO System




b=3.2 cm







Matching Left and Right





3D reconstruction





Stereo: Disparity Map







Using real-time stereo vision for mobile robot navigation

Don Murray


Jim Little

Computer Science Dept. University of British Columbia Vancouver, BC, Canada V6T 1Z4




Depth Map in a City







Another Example (Hole Filling)



Cloth Parameters and Motion Capture by David Pritchard B.A.Sc., University of Waterloo, 2001



Stereo Vision

Large number of algorithms out there:


http://vision.middlebury.edu/stereo/

rank 43 different algorithms.




Object recognition

source: http://www.cs.cornell.edu/courses/cs4670/2013fa/




Pedestrian and car detection



Lane detection





Coral classification



Bag of words

Object

Bag of 'words'











Appearance-based place recognition









source: http://www.robots.ox.ac.uk/~mjc



Deep learning based classification







Computer Vision Books

- Richard Szeliski, "Computer Vision: Algorithms and Applications", Springer, 2010
- Richard Hartley and Andrew Zisserman,
 "Multiple View Geometry in Computer Vision",
 Cambridge University Press, 2004
- David Forsyth and Jean Ponce, "Computer Vision: A Modern Approach", Pearson, 2011



Nice Classes

- Noah Snavely Introduction to Computer Vision http://www.cs.cornell.edu/courses/
 cs4670/2013fa/lectures/lectures.html
- Steve Seitz and Rick Szeliski Computer Vision http://courses.cs.washington.edu/courses/ cse576/08sp/

